						Date		No.	TS	S-EQ10I01	04	0
TEM	LINED Y-TY	YPF 9	STRA	INFR		CODE	STR-YT	-1A-C		FC	ORM NO.	
ESCRIPTIO					olded lining.		<u> </u>					
USTOMER	,			•			PROJECT					
ONSULTAN	т						REF.					
UST.SPEC.												
15000			1		_ ==		Part	Descr.	M	laterial		
						200	1	Body		AST DUCTI ASTM A39		
	4	4					2	Cover		ARBON STI ASTM A36		
16	Mhuumhii			mmin	minim		3	Cover Linir	ıg P	FA		
		din					4	Basket	Р	TFE		
6		The second	110	9	mmmm	ann.	7	Drain liner	Р	TFE		
		13		KIN			8	Drain plug	s	S304		
H		10	E				9	Lining		PFA		
	dill the second						Flange	drilling		⊠ ANSI B16.5 / B16.42 150#		
		(II)) (7	3		Exterio	r Finish		Enamel pr	imer	
					8)							
					8)		Service c	onditions			Tables	
					8)			onditions Design			Testing	
						Press.	max.), bar			- Hydro	Testing	bar
SIZE	Tag No.	н	L	Lin. Thk. X	Qty	Press.		Design		-Hydro Spark		
NB	rag No.			Lin. Thk. X (min.)		Press.	max.), bar max.), °C	Design		Spark Vacuum	Body	bar KV mm H
	rag No.	H 125	L 160 200	Lin. Thk. X		Press. Temp. Vac. (m	max.), bar max.), °C	Design		Spark	Body	bar KV
NB 1"	rag No.	125	160	Lin. Thk. X (min.) 3.0		Press. Temp. Vac. (m	max.), bar max.), °C ax.), mm H	Design		Spark Vacuum	Body	bar KV mm H
1" 11/2" 2" 3"	Tag No.	125 150	160 200 230 310	Lin. Thk. X (min.) 3.0 3.0 3.0		Press. Temp. Vac. (m Fluid Notes: 1. Al	max.), bar max.), °C ax.), mm H	Design Ig s in mm.		Spark Vacuum	Body	bar KV mm H
1" 11/2" 2"	Tag No.	125 150 160	160 200 230	Lin. Thk. X (min.) 3.0 3.0		Press. Temp. Vac. (m Fluid Notes: 1. Al 2. Ve 3. Lii	max.), bar max.), °C ax.), mm H dimension int holes prining in acco	s in mm. ovided. ordance to A	Oper.	Spark Vacuum Pneumatic	Body	bar KV mm H
1" 11/2" 2" 3"	Tag No.	125 150 160 220	160 200 230 310	Lin. Thk. X (min.) 3.0 3.0 3.0		Press. Temp. Vac. (n Fluid Notes: 1. Al 2. Ve 3. Liii 4. Re 5. Lii	max.), bar max.), °C ax.), mm H dimension int holes prining in acco	s in mm. ovided. ordance to A	Oper.	Spark Vacuum Pneumatic	Body	bar KV mm H
1" 11/2" 2" 3"	Tag No.	125 150 160 220	160 200 230 310	Lin. Thk. X (min.) 3.0 3.0 3.0		Press. Temp. Vac. (m Fluid Notes 1. Al 2. Ve 3. Lii 4. Re	max.), bar max.), °C ax.), mm H dimension int holes prining in acco	s in mm. ovided. ordance to A 16.5 150# f	Oper.	Spark Vacuum Pneumatic	Body	bar KV mm H
1" 11/2" 2" 3"	Tag No.	125 150 160 220	160 200 230 310	Lin. Thk. X (min.) 3.0 3.0 3.0		Press. Temp. Vac. (n Fluid Notes: 1. Al 2. Ve 3. Liii 4. Re 5. Lii	max.), bar max.), °C ax.), mm H dimension int holes prining in acco	s in mm. ovided. ordance to A 16.5 150# f	Oper.	Spark Vacuum Pneumatic	Body	bar KV mm H
NB 1" 11/2" 2" 3" 4"	Tag No.	125 150 160 220	160 200 230 310	Lin. Thk. X (min.) 3.0 3.0 3.0		Press. Temp. Vac. (n Fluid Notes: 1. Al 2. Ve 3. Liii 4. Re 5. Lii	max.), bar max.), °C ax.), mm H dimension int holes prining in acco	s in mm. ovided. ordance to A 16.5 150# f	Oper.	Spark Vacuum Pneumatic	Body	bar KV mm H
NB 1" 11/2" 2" 3" 4"	Tag No.	125 150 160 220	160 200 230 310	Lin. Thk. X (min.) 3.0 3.0 3.0		Press. Temp. Vac. (n Fluid Notes: 1. Al 2. Ve 3. Liii 4. Re 5. Lii	max.), bar max.), °C ax.), mm H dimension int holes prining in acco	s in mm. ovided. ordance to A 16.5 150# f	Oper.	Spark Vacuum Pneumatic	Body	bar KV mm H
NB 1" 11/2" 2" 3" 4"	Tag No.	125 150 160 220	160 200 230 310	Lin. Thk. X (min.) 3.0 3.0 3.0		Press. Temp. Vac. (n Fluid Notes: 1. Al 2. Ve 3. Liii 4. Re 5. Lii	max.), bar max.), °C ax.), mm H dimension int holes prining in acco	s in mm. ovided. ordance to A 16.5 150# f	Oper.	Spark Vacuum Pneumatic	Body	bar KV mm H

GIE Inc., Global Industrial Equipment, Inc. • 2434 Darnell Drive • Spring Valley, Ohio 45370 • TOLL FREE: 1-888-2-GET-GIE (1-888-243-8443) • PHONE: (937) 862-9500 • FAX: (937) 862-9501